

# SIGNAL ENHANCEMENT PRODUCTS

## 150 - 512 MHz

### ELECTRICAL SPECIFICATIONS

Model Number	2492/T	2492/T2	2492/T4	2592/T	2592/T2	2592/T4
Frequency Band	150-174	150-174	150-174	406-512	406-512	406-512
Coupling Range	6-25 dB	6-25 dB	6-25 dB	6-25 dB	6-25 dB	6-25 dB
# of Tap Points	1	2	4	1	2	4
Input Power	250 Watts	250 Watts	250 Watts	250 Watts	250 Watts	250 Watts
Nominal Impedance	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω
Temperature Range	- 22 to +140 °F - 30 to +60 ° C	- 22 to +140 °F - 30 to +60 ° C	- 22 to +140 °F - 30 to +60 ° C	- 22 to +140 °F - 30 to +60 ° C	- 22 to +140 °F - 30 to +60 ° C	- 22 to +140 °F - 30 to +60 ° C
List Price	\$205.00	\$270.00	\$400.00	\$185.00	\$250.00	\$380.00

### MECHANICAL SPECIFICATIONS

Connectors	N Female	N Female	N Female	N Female	N Female	N Female
Finish	EMR Gray	EMR Gray	EMR Gray	EMR Gray	EMR Gray	EMR Gray
Actual Dimensions						
Inches	11 3/4 x 1 x 1 7/8	11 3/4 x 1 x 2 3/4	24 3/8 x 1 x 2 3/4	8 x 1 x 1 7/8	8 x 1 x 2 3/4	14 1/2 x 1 x 2 3/4
Metric	299 x 26 x 48	299 x 26 x 70	620 x 26 x 70	204 x 26 x 48	204 x 26 x 70	369 x 26 x 70
Ship Wt.						
lbs	3	3	4	2	2	3
kg	1.4	1.4	1.9	1.0	1.0	1.4



2492/T



2492/T2



2592/T



2592/T2



2592/T4