

SIGNAL ENHANCEMENT PRODUCTS

806 - 960 MHz

ELECTRICAL SPECIFICATIONS

Model Number	2692/T-8	2692/T2-8	2692/T4-8	2692/T-9	2692/T2-9	2692/T4-9
Frequency Band	806-894	806-894	806-894	894-960	894-960	894-960
Coupling Range	6-25 dB	6-25 dB	6-25 dB	6-25 dB	6-25 dB	6-25 dB
# of Tap Points	1	2	4	1	2	4
Input Power	250 Watts	250 Watts	250 Watts	250 Watts	250 Watts	250 Watts
Nominal Impedance	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω
Temperature Range	- 22 to +140 °F - 30 to 60 ° C	- 22 to +140 °F - 30 to 60 ° C	- 22 to +140 °F - 30 to 60 ° C	- 22 to +140 °F - 30 to 60 ° C	- 22 to +140 °F - 30 to 60 ° C	- 22 to +140 °F - 30 to 60 ° C
List Price	\$175.00	\$245.00	\$370.00	\$175.00	\$245.00	\$370.00

MECHANICAL SPECIFICATIONS

Connectors	N Female	N Female	N Female	N Female	N Female	N Female
Finish	EMR Gray	EMR Gray	EMR Gray	EMR Gray	EMR Gray	EMR Gray
Actual Dimensions						
Inches	5 1/2 x 1 x 1 7/8	5 1/2 x 1 x 2 3/4	11 x 1 x 2 3/4	5 1/2 x 1 x 1 7/8	5 1/2 x 1 x 2 3/4	11 x 1 x 2 3/4
Metric	140 x 26 x 48	140 x 26 x 70	280 x 26 x 70	140 x 26 x 48	140 x 26 x 70	280 x 26 x 70
Ship Wt.						
lbs	2	2	3	2	2	3
kg	1.0	1.0	1.4	1.0	1.0	1.4

2692/T-8



2692/T-9



2692/T2-8



2692/T2-9



2692/T4-8



2692/T4-9

