

MULTICOUPLER COMPONENTS


30 - 960 MHz

ELECTRICAL SPECIFICATIONS

Model Number	2302-1/A	2302-0/A	2304-1/A	2304-0/A	2308-1/A	2308-0/A
Frequency Band (MHz)	30-512	30-512	30-512	30-512	30-512	30-512
Application	Receiver	Receiver	Receiver	Receiver	Receiver	Receiver
Type	2-Way	2-Way	4-Way	4-Way	8-Way	8-Way
Isolation	20 dB min.	20 dB min.	20 dB min.	20 dB min.	20 dB min.	20 dB min.
List Price	\$115.00	\$140.00	\$140.00	\$180.00	\$300.00	\$380.00

MECHANICAL SPECIFICATIONS

Dimensions: Inches	1 x 2 1/4 x 3 1/4	1 1/2 x 2 3/4 x 3 3/8	1 x 3 3/4 x 4 1/8	1 1/2 x 4 3/4 x 4 1/2	1 x 6 3/4 x 5 1/4	1 1/2 x 8 1/2 x 5 3/4
Metric	26 x 58 x 83	39 x 70 x 86	26 x 96 x 105	39 x 70 x 86	26 x 172 x 134	39 x 216 x 147
Connectors: Input	BNC Female	N Female	BNC Female	N Female	BNC Female	N Female
Output	BNC Female	N Female	BNC Female	N Female	BNC Female	N Female
Ship Weight: lbs.	2	2	2	3	2	4
kg.	1.0	1.0	1.0	1.4	1.0	1.9




ELECTRICAL SPECIFICATIONS

Model Number	2602-1/C	2602-0/C	2604-1/C	2604-0/C	2608-1/C	2608-0/C
Frequency Band (MHz)	800-960	800-960	800-960	800-960	800-960	800-960
Application	Receiver	Receiver	Receiver	Receiver	Receiver	Receiver
Type	2-Way	2-Way	4-Way	4-Way	8-Way	8-Way
Isolation	20 dB min.	20 dB min.	20 dB min.	20 dB min.	20 dB min.	20 dB min.
List Price	\$115.00	\$140.00	\$140.00	\$180.00	\$300.00	\$380.00

MECHANICAL SPECIFICATIONS

Dimensions: Inches	1 x 2 1/4 x 3 1/4	1 1/2 x 2 3/4 x 3 3/8	1 x 3 3/4 x 4 1/8	1 1/2 x 4 3/4 x 4 1/2	1 x 6 3/4 x 5 1/4	1 1/2 x 8 1/2 x 5 3/4
Metric	26 x 58 x 83	39 x 70 x 86	26 x 96 x 105	39 x 70 x 86	26 x 172 x 134	39 x 216 x 147
Connectors: Input	BNC Female	N Female	BNC Female	N Female	BNC Female	N Female
Output	BNC Female	N Female	BNC Female	N Female	BNC Female	N Female
Ship Weight: lbs.	2	2	2	3	4	4
kg.	1.0	1.0	1.0	1.4	1.9	1.9



POWER DIVIDERS, RECEIVER